



ELECTRICAL CHARACTERISTICS:

THERMISTOR:
 R @ 25 °C = 2K OHMS ±1%
 RT CURVE = Y
 NTC = -3.9%/°C @ 25°C

OPERATING TEMPERATURE: 0°C TO 60°C
 STORAGE TEMPERATURE: 0°C TO 60°C

MECHANICAL CHARACTERISTICS:

LEADS:
 #24 AWG TIN PLATED COPPER
 CONDUCTOR
 BELDEN 1508A CABLE

HOUSING:
 316 STAINLESS STEEL HOUSING, POLISHED
 DELRIN HANDLE, SLIP FIT WITH TUBE

CONNECTOR: STRIPPED ENDS

DEPARTMENT APPROVALS

ENG APPR. _____
 Q.A. APPR. _____

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES

TOLERANCES:
 FRACTIONAL ±1/8
 X ±0.1
 .XX ±0.02
 .XXX ±0.005

THIS SYMBOL DENOTES CRITICAL INSPECTION DIMENSIONS/FEATURES

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
 QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS
 PROHIBITED.

INITIAL RELEASE	07/24/2023	CL
REV.	DESCRIPTION	DATE INITIALS
6		
5		

SCALE: 1:8 SHEET SIZE **B** SHEET 1 OF 1